

DLV30S/45S/70S-AYK Serie

Multi-Speed bürstenloser DELVO Elektroschrauber mit Zählfunktion



Setting Range of MAX 650 min ⁻¹ Series					Setting Range of MAX 1,200 min ⁻¹ Series				Setting Range of MAX 2,000 min ⁻¹ Series		
		DLV30S06	DLV45S06	DLV70S06			DLV30S12	DLV45S12			DLV30S20
Speed Level	Speed (min ⁻¹)	Torque (Nm)			Speed Level	Speed (min ⁻¹)	Torque (Nm)		Speed Level	Speed (min ⁻¹)	Torque (Nm)
Lv1	160	0.4 - 1.3	—	—	Lv1	300	0.4 - 0.6	—	Lv1	500	0.4
Lv2	220	0.4 - 2.0	2.0 - 2.4	—	Lv2	420	0.4 - 1.2	—	Lv2	690	0.4 - 0.8
Lv3	280	0.4 - 2.7	2.0 - 3.5	3.8	Lv3	530	0.4 - 1.8	2.0	Lv3	880	0.4 - 1.2
Lv4	340	0.4 - 3.0	2.0 - 4.5	3.8 - 4.6	Lv4	640	0.4 - 2.4	2.0 - 2.6	Lv4	1,060	0.4 - 1.6
Lv5	410	0.4 - 3.0	2.0 - 4.5	3.8 - 5.4	Lv5	750	0.4 - 3.0	2.0 - 3.2	Lv5	1,250	0.4 - 2.0
Lv6	470	0.4 - 3.0	2.0 - 4.5	3.8 - 6.2	Lv6	860	0.4 - 3.0	2.0 - 3.8	Lv6	1,440	0.4 - 2.4
Lv7	530	0.4 - 3.0	2.0 - 4.5	3.8 - 7.0	Lv7	980	0.4 - 3.0	2.0 - 4.4	Lv7	1,630	0.4 - 2.8
Lv8	590	0.4 - 3.0	2.0 - 4.5	3.8 - 7.0	Lv8	1,090	0.4 - 3.0	2.0 - 4.5	Lv8	1,810	0.4 - 3.0
Lv9	650	0.4 - 3.0	2.0 - 4.5	3.8 - 7.0	Lv9	1,200	0.4 - 3.0	2.0 - 4.5	Lv9	2,000	0.4 - 3.0

- automatische 3-stufige Geschwindigkeitssteuerung
- 3-stufiges Verschrauben
- Auto-Reverse-Funktion
- Bit-Bremsfunktion
- Systemmeldungen im LED Display am Schrauber
- Ein-/Ausgangsschnittstelle zur Einbindung in externe Steuerungssysteme (Artikelnr.: DLW9090)
- Verbindungsfunktion von bis zu 10 Schrauber
- Einstellungen am Schrauber über Fernbedienung (optional) möglich (Artikelnr.: RC1000)

Modell	Drehmoment Nm	Drehzahl U/min	Ausführung	Steuergerät
Serie DLV30...-AYK				
DLV30S06P-AYK	0,4 - 3,0 Nm	160-650	ESD, Schubstart	DEA0151N-AZ
DLV30S06L-AYK	0,4 - 3,0 Nm	160-650	ESD, Hebelstart	DEA0151N-AZ
DLV30S12P-AYK	0,4 - 3,0 Nm	300-1.200	ESD, Schubstart	DEA0151N-AZ
DLV30S12L-AYK	0,4 - 3,0 Nm	300-1.200	ESD, Hebelstart	DEA0151N-AZ
DLV30S20P-AYK	0,4 - 3,0 Nm	500-2.000	ESD, Schubstart	DEA0241N-AZ
DLV30S20L-AYK	0,4 - 3,0 Nm	500-2.000	ESD, Hebelstart	DEA0241N-AZ
Serie DLV45...-AYK				
DLV45S06P-AYK	2,0 - 4,5 Nm	160-650	ESD, Schubstart	DEA0151N-AZ
DLV45S06L-AYK	2,0 - 4,5 Nm	160-650	ESD, Hebelstart	DEA0151N-AZ
DLV45S12P-AYK	2,0 - 4,5 Nm	300-1.200	ESD, Schubstart	DEA0241N-AZ
DLV45S12L-AYK	2,0 - 4,5 Nm	300-1.200	ESD, Hebelstart	DEA0241N-AZ
Serie DLV70...-AYK				
DLV70S06P-AYK	3,8 - 7,0 Nm	160-650	ESD, Schubstart	DEA0241N-AZ
DLV70S06L-AYK	3,8 - 7,0 Nm	160-650	ESD, Hebelstart	DEA0241N-AZ